

# Telco marine heater – T2RIB

Type	El number 230V	El number 400V	Power	Height inkl. grille	Height	Length	Depth	Description
T2RIB 025	54 494 56	54 494 57	250 W	238 mm	150 mm	379 mm	96 mm	Ship heater with power switch Bi-metal thermostat, Thermal cut-out and protection grille.
T2RIB 03	54 494 60	54 494 61	300 W	238 mm	150 mm	379 mm	96 mm	
T2RIB 04	54 494 64	54 494 65	400 W	238 mm	150 mm	379 mm	96 mm	
T2RIB 08	54 494 68	54 494 69	800 W	238 mm	150 mm	629 mm	96 mm	
T2RIB 12	54 494 72	54 494 73	1200 W	238 mm	150 mm	869 mm	96 mm	
T2RIB 16	54 494 76	54 494 77	1600 W	238 mm	150 mm	1134 mm	96 mm	
T2RIB 20	54 494 90	54 494 91	2000 W	238 mm	150 mm	1395 mm	96 mm	

A powerhouse in a small frame, the T2RIB 16 offers an output of 1600 W from an area of less than 2 sq. ft., while the surface temperature remains below the maximum limit stipulated for electric heaters.

Constructed in aluminum and stainless steel, the lightweight T2RIB is ideal for ships and offshore installations which impose space and weight limitations.

T2RIB has been approved by Norwegian risk-assessment foundation Det Norske Veritas with the classification IP 44 for use in wet and dry rooms on ships and offshore installations. It's a good option where space and weight are important factors when choosing a heating source for example in bathrooms and WCs

The heater features a protection grating at the top to prevent it from being covered, and an automatic thermal cut-out to avert overheating.



Specifications
Flow-through marine heater with on/off switch, bi-metal thermostat, thermal cut-out and protection grille.
230 V and 400V
Colour: Pearl white
Connection: Right-hand side
Fitting to walls: Heaters must be fitted horizontally and are delivered with solid wall brackets.
Max. surface temperature: 84°C
Classification: IP 44. This heater is particularly suited for use in damp environment, e.g. bathrooms and toilets

Installation distance requirements	T2RIB
Minimum distance to side wall:	2 cm
Minimum distance to floor:	5 cm
Minimum distance to ceiling or window sill:	38 cm