

Telco Nursery heaters – TIL / TL

Type	El-number	Power	Height	Length	Depth	Description
TIL 04	54 490 40	400 W	150 mm	682 mm	86 mm	Low-temperature nursery heater, with switchbox for permanent installation
TIL 08	54 490 41	800 W	150 mm	1157 mm	86 mm	
TL 04	54 490 42	400 W	150 mm	632 mm	86 mm	Low-temperature nursery heater, for external controls and permanent installation.
TL 08	54 490 43	800 W	150 mm	1107 mm	86 mm	

Heaters type TIL and TL are low-temperature heaters with special approval for use in nurseries. The surface temperature of the heater is so low that no thermal cut-out is required. The heaters are equipped with a slanted protection grille to prevent accidental covering. The grille also prevents foreign objects from entering the heater, for example fingers. This is a very child-friendly heater with a low surface temperature of less than 60°C.

The heaters are manufactured from extruded aluminium sections. The complete heating element is also made from aluminium and incorporates a heating coil, insulation, cooling fins and connection lead in one unit. This is a tried and tested design that provides excellent heat distribution and a long lifetime.

TIL and TL can both be lacquered in special colours.



TIL



TL

Specifications
Flow-through low temperature heater with protection grille.
230 V
Colour: Pearl white
Splashproof and rustproof; can be used in wet rooms.
Connection: Right-hand side
Fitting to walls: Heaters must be fitted horizontally and are delivered with solid wall brackets.
Max. surface temperature: 59°C

Installation distance requirements	TIL / TL
Minimum distance to side wall:	2 cm
Minimum distance to floor:	5 cm
Minimum distance to ceiling or window sill:	15 cm