

Low-temperatur skirting heater - TRLU

Type	El-number	Power	Height	Length	Depth	Description
TRLU 08	54 493 10	800 W	79 mm	2303 mm	83 mm	Low-temperature skirting heater with thermal cut-out. For external control.
Floor brackets TRLU	54 493 50					

The heater is manufactured from extruded aluminum sections. The complete heating element is also made from aluminum and incorporates a heating coil, insulation, cooling fins and connection lead in one unit. This is a tried and tested design that provides excellent heat distribution and a long lifetime.

The heater must be fitted horizontally and is supplied with solid aluminum mountings. Installation on the floor close to the wall is possible using special floor brackets. Standard connection: Right hand side.

TRLU can be lacquered in special colours and supplied with curtain clamps and floor brackets.



Spesifications
Flow-through heater for external control and permanent installation.
230 V
Colour: Pearl white
Splashproof and rustproof; can be used in wet rooms.
Connection: Right-hand side
Fitting to walls: Heaters must be fitted horizontally and are delivered with sturdy wall brackets.
Floor installation: Heaters can be fitted to the floor using floor brackets that need to be ordered separately
Max. surface temperature: 57°C

Installation distance requirements	TRLU
Minimum distance to side wall:	2 cm
Minimum distance to floor:	5 cm
Minimum distance to ceiling or window sill:	15 cm